

SPECIFICATIONS

M125Z



TOYO
TIRES

M125Z

The **M125Z** from Toyo Tires is a highway rib, all-position tyre designed primarily for steer axle use.

The M125Z features a defence groove to prevent shoulder wear.

Steer axle – most suitable, drive axle – suitable, trailer – suitable



Features & Benefits



Wide five rib pattern with wide shoulder ribs

A wide contact patch for optimum traction and resistance to shoulder wear



Wear resistant tread compound

Improved traction in wet and muddy conditions



Defence groove on outside of tread shoulder

Resistance to shoulder wear



High-elongation cord top steel belt

Superior retreadability

Suitability



Size & Specifications

Tyre Size	Load/Speed Rating	Speed Rating	Tread Depth (mm)	Inflated Dim.		Weight (kgs)	Max Load (kgs)	Max Cold Pressure (kPa)	Measuring Rim Width (inch)	Approved Rim Width Codes (inch)
				O.D. (mm)	O.W. (mm)					
225/90R17.5	127L	L	12.3	856	224	31.6	1750	700	6.75	6.0 - 6.75

TOYO TIRES®



Find a dealer



1800 454 065



Toyo Tyre & Rubber Australia Limited
137-149 Airds Road, Minto, NSW 2566

Visit us at **toyotires.com.au**