



FUELED BY ENTHUSIASTS

RIDGE GRAPPLER™

PRODUCT DATA SHEET

Version 1.10

The Ridge Grappler® represents the next generation of the Grappler family, blending the durability of the Trail Grappler® M/T with the comfort and longevity of Terra Grappler® A/Ts to provide keen 4WDers with a true do-it-all tyre.

	METRIC	IMPERIAL
RIM SIZE (INCH):	15 - 20	17 - 22
SERIES:	65 - 75	
DIAMETER (INCH):		33 - 37
WIDTH (MM/INCH):	265 - 315	12.50 - 13.50
SPEED RATING:	Q & T	Q

BEST FIT?

The Ridge Grappler® suits the plus-sized demands of serious off-roaders, perfect for the Toyota HiLux, Landcruiser or Prado, Nissan Patrol or Navara, Mitsubishi Pajero or Triton, Ford Ranger or Everest, Isuzu D-Max or MU-X and Mazda BT-50.



HYBRID EXTREME-DUTY LIGHT-TRUCK 4X4 TYRE



2-PLY OR 3-PLY, YOU CHOOSE

All imperial sizes and some metric sizes use heavy-duty, 3-ply construction similar to the Trail Grappler® M/T while most metric sizes use a lighter, 2-ply construction that's still a step up from Terra Grappler® A/Ts, increasing comfort and flexibility.



ALTERNATING SHOULDER GROOVES

Shoulder grooves are arranged in varied widths and lengths to clear mud and maintain traction. Lateral Z grooves are set in a zig-zag pattern to provide biting edges for traction.



STEPPED BLOCK EDGES

Alternating tapered edges and stepped block edges provide cut-through and additional biting edges on slick, hard surfaces.



STAGGERED SHOULDER LUGS

Alternating shoulder tread provides additional off-road traction, increasing contact with rut edges or rocks with the ability to paddle through soft terrain.



DUAL SIDEWALL DESIGNS

Like all Grapplers, the Ridge Grappler® features two bold sidewall designs. One side features a more traditional pattern while the other side features a new, aggressive block design.



FUELED BY ENTHUSIASTS

PRODUCT DATA SHEET

Version 1.10

Tyre Size	Load Index/Speed Symbol	Ply Rating / Ply Count	Tread Depth (mm)	Inflated Dimensions		Measuring Rim Width (in)	Approved Rim Widths (in)
				Overall Dia. (mm)	Overall Width (mm)		
LT245/70R16	118Q	10/2	13.0	750	248	7.0	6.5 - 8.0
LT305/70R16	124Q	10/3	13.0	834	311	9.0	8.0 - 10.0
LT315/75R16	127Q	10/3	13.0	878	313	8.5	8.0 - 10.5
LT265/70R17	121Q	10/2	13	804	272	8.0	7.0 - 9.0
LT285/70R17	121Q	10/2	13	832	292	8.5	7.5 - 9.0
LT295/70R17	121Q	10/3	13	846	299	8.5	7.5 - 10.0
LT305/70R17	121Q	10/3	13	860	311	9.0	8.0 - 10
LT315/70R17	121Q	10/3	13	874	323	9.5	8.0 - 10.5
LT285/75R17	121Q	10/3	13	860	286	8.0	7.5 - 9.5
LT33x12.50R17	120Q	10/3	14.5	832	318	10.0	8.5 - 11.0
LT35x12.50R17	121Q	10/3	14.5	883	318	10.0	8.5 - 11.0
LT37x12.50R17	124Q	8/3	14.5	934	318	10.0	8.5 - 11.0
LT37x13.50R17	121Q	10/3	14.5	934	345	11.0	9.0 - 11.5
LT285/60R18	122Q	10/2	13	805	292	8.5	8.0 - 10.0
LT265/65R18	122Q	10/2	13	807	272	8.0	7.5 - 9.5
LT275/65R18	123Q	10/2	13	815	279	8.0	7.5 - 9.0
LT285/65R18	125Q	10/2	13	827	292	8.5	8.0 - 10.0
LT305/65R18	128Q	12/3	13	853	311	9.0	8.5 - 11.0
LT265/70R18	124Q	10/2	13	835	272	8.0	7.0 - 9.0
LT275/70R18	125Q	10/2	13	843	279	8.0	7.0 - 8.5
LT285/70R18	127Q	10/2	13	863	181	8.5	7.5 - 9.5
LT295/70R18	129Q	10/3	13	871	299	8.5	7.5 - 10.0
LT33x12.50R18	122Q	12/3	14.5	832	318	10.0	8.5 - 11.0
LT35x12.50R18	128Q	12/3	14.5	883	318	10.0	8.5 - 11.0
LT37x12.50R18	128Q	10/3	14.5	934	318	10.0	8.5 - 11.0
LT37x13.50R18	124Q	8/3	14.5	934	345	11.0	9.5 - 12.0
265/50R20	111T	N/A	10.7	774	277	8.5	7.5 - 9.5
LT275/55R20	120Q	10/2	13	816	284	8.5	7.5 - 9.5
275/55R20	117T	N/A	10.7	810	284	8.5	7.5 - 9.5
LT285/55R20	117Q	8/2	13	828	297	9.0	8.0 - 10.0
LT305/55R20	125Q	12/2	13	844	316	9.5	8.5 - 11.0
LT295/60R20	126Q	10/2	13	862	299	8.5	8.0 - 10.0
LT275/65R20	126Q	10/2	13	866	279	8.0	7.5 - 9.5
LT33x12.50R20	119Q	12/3	14.5	832	318	10.0	8.5 - 11.0
LT35x12.50R20	125Q	12/3	14.5	883	318	10.0	8.5 - 11.0
LT37x12.50R20	126Q	10/3	14.5	934	318	10.0	8.5 - 11.0
LT37x13.50R20	127Q	10/8	14.5	934	345	11.0	9.5 - 12.0
LT33x12.50R22	114Q	12/3	14.5	832	318	10.0	8.5 - 11.0
LT35x12.50R22	121Q	12/3	14.5	883	318	10.0	8.5 - 11.0