

The Terra Grappler G2® is Nitto's next generation all-terrain tyre, specifically designed to tackle your everyday on- and off-road adventures, whether you're commuting to work, towing a trailer or headed up to your favourite mountain trail.

RIM SIZE: 16 - 22 INCH
SERIES: 45 - 75
WIDTH: 225 - 305
SPEED RATING: Q, S, T & H

BEST FIT?

The Terra Grappler G2® suits daily drivers who like to head off the beaten track from time to time, perfect for the Toyota HiLux, Landcruiser or Prado, Nissan Patrol or Navara, Mitsubishi Pajero or Triton, Ford Ranger or Everest and Isuzu D-Max or MU-X.




ALL-TERRAIN 4X4 TYRE




DUAL SIDEWALL DESIGNS

Each Grappler has two sidewall designs so you can choose how your tyres look. On the Terra Grappler G2®, one side features an aggressive version of the original Terra Grappler thunderbolt while the other displays a new blade design.



RIGID COUPLING JOINTS

Reinforced coupling joints between the outermost and central tread blocks minimise excessive tread flex, maximising traction and steering response while encouraging even wear.




FULL-DEPTH SIPES

Siping helps resist hydroplaning by cutting through pockets of water on road surfaces. Full-depth siping equal to the tread depth offers additional biting edges in wet conditions while also maintaining tread design as the tyre wears.



SHOULDER LUGS

Staggered shoulder lugs provide additional biting edges in off-road conditions, especially in deep sand and loose dirt. Furthermore, new sidewall designs connect these lugs from the shoulder block down to the middle of the sidewall surface for additional strength.



VARIABLE-PITCH TREAD BLOCKS

Computer analysis of tread block arrangements has allowed Nitto's engineers to minimise the tyre noise normally heard while driving at highway speeds.



TERRA GRAPPLER G2

FUELED BY ENTHUSIASTS

PRODUCT DATA SHEET
Version 1.10



Tyre Size	Load Index/Speed Symbol	Ply Rating / Ply Count	Tread Depth (mm)	Inflated Dimensions		Measuring Rim Width (in)	Approved Rim Widths (in)
				Overall Dia. (mm)	Overall Width (mm)		
265/70R16	116T	N/A	10.4	778	272	8.0	7.0 - 9.0
LT265/75R16	123Q	10/2	13.3	804	266	7.5	7.0 - 9.0
LT285/75R16	126Q	10/2	13.5	834	286	8.0	7.5 - 9.5
225/65R17	106H	N/A	9.9	724	228	6.5	6.0 - 8.0
265/65R17	116T	N/A	10.2	776	272	8.0	7.5 - 9.5
255/70R17	116S	N/A	10.3	790	260	7.5	6.5 - 8.5
265/70R17	115T	N/A	10.4	804	272	8.0	7.0 - 9.0
265/60R18	114T	N/A	10.2	775	272	8.0	7.5 - 9.5
285/60R18	120S	N/A	10.8	799	292	8.5	8.0 - 10.0
LT265/65R18	122R	10/2	12.7	801	272	8.0	7.5 - 9.5
265/70R18	116T	N/A	10.4	829	272	8.0	7.0 - 9.0
LT285/65R18	125R	10/2	13.9	833	292	8.5	8.0 - 10.0
265/50R20	111S	N/A	10.6	774	277	8.5	7.5 - 9.5
275/60R20	116S	N/A	10.3	838	279	8.0	7.5 - 9.5
285/50R20	116S	N/A	10.8	794	297	9.0	8.0 - 10.0
305/55R20	116S	N/A	10.6	844	316	9.5	8.5 - 11.0
285/45R22	114H	N/A	10.8	815	285	9.5	9.0 - 10.5